

L300 Tack Tank

LeeBoy



Perfect for the all-inclusive commercial paving contractor, the L300 Tack Distributor provides a perfectly sized tank for small to large projects including parking lots, patching, driveways or soil stabilization. Daily task can be completed with ease by relying on the trouble-free Honda powered engine and the proven reliable user-friendly design. Uniquely configurable, the customizable options give the contractor the ability to create a solution specific to their exact needs.

Performance Features:

- 300 Gallon (1,136 l) Capacity Tank
- 4.8 hp (3.6 kw) Honda Engine
- 6' (1.8 m) Wand with On/Off Valve
- 40' (12.19 m) Heavy-Duty Recoil Hose Reel
- 4,210 lbs (1,909 kg) Loaded Weight
- 1" (25 mm) Rear Tank Sampling Valve
- One 300,000 BTU Propane Burner
- Trailer-Mounted or Skid-Mounted Configurations
- Electric brakes
- Emergency Brake-Away System
- Optional Accessories Available



L300 Tack Distributor Specifications



Tank Size	300 gallons (1,136 l)
Dimensions (Trailer Configuration)	- Length: 12' 1" (3.68 m) - Width: 6' 4" (1.94 m) - Height: 5' 9" (1.76 m) - Shipping Weight: 1,760 lbs (798 kg)
Dimensions (Skid Configuration)	- Length: 8' 10" (2.69 m) - Width: 4' 3" (1.28 m) - Height: 4' 9" (1.45 m)
Engine	Honda – 4.8 hp (3.6 kw)
Capacities	- Fuel: 1 gallon (3.79 l)
Tank Dimensions	- Length: 52" (1.32 m) - Width: 54.125" (1.37 m) - Height: 36.25" (.92 m)
Asphalt Pump	- Specially designed 7 gallons per minute (26.5 lmp) pump
Heat System	- One 300,000 BTU propane burner - One start burner - 40 lbs (18.1 kg) propane fuel tank
Temperature Gauge	- 50 - 300° F (10 - 149° C) - Adjustable angle faceplate
Flush Tank	- 7 gallons (26.5 l) tank with suck back valve
Hose and Reel	- .5" x 40' (13 mm x 12.19 m) heavy-duty recoil hose reel

Wand	- 6' (1.829 m) wand with cold handles - On/off valve - Removable spray tip
Manhole	- 20" (508 mm) diameter - 10" (254 cm) diameter fill hole - 3 psi (2.1 bar) pressure relief
Clean Out	- 4" (102 mm)
Sampling Valve	- 1" (25 mm)
Additional Standard Equipment	- Waste bucket mount (trailer only) - 1" rear tank return - 2" in-tank overflow
Optional Equipment	Engines - Honda gas - 4.8 hp (3.6 kW) electric start - Hatz diesel - 7.2 hp (5.4 kW) pull start or electric start Fuel: 1.32 gallons (5.0 l) Heat Systems - Diesel Burner One 300,000 BTU diesel burner (only available with electric start engines) 7 gallon (26.5 l) fuel tank Auto ignition diesel burner with outfire - Overnight Heat 120 volt/1500 watt Immersion element Spray bar - Spray width: 12' (3.65 m) - Spray Bar Controls: In-truck wireless remote controls (requires spray bar option) - Spray bar lift with wireless remote control Insulated Tank 2-5/16" ball hitch



ST Engineering LeeBoy, Inc. ■ 500 Lincoln County Parkway Extension ■ Lincolnton, NC 28092 ■ 704.966.3300
www.LeeBoy.com

LeeBoy and the LeeBoy logo are registered trademarks of ST Engineering LeeBoy, Inc. Equipment model names, slogans and subsidiary logos appearing in this collateral may be registered trademarks or the trademarks of ST Engineering LeeBoy, Inc. The technical data contained herein is subject to change due to continuous engineering and development. Accordingly, LeeBoy reserves the right to modify at any time. © 2020 ST Engineering LeeBoy, Inc. All rights reserved. BR-4004.6-EN

